Conex | Bänninger



Conex Bänninger Press Fitting Lubricant

Conex Bänninger press fitting lubricant is used to help ease tube insertion, ensuring that the tube does not dislodge the O-ring when it is being inserted.

The lubricant on a press fitting O-ring if stored or left outside of its packaging may lose some of its lubricity over time. It is therefore good practice in such cases to add a small amount of lubricant to the O-ring.

Conex Bänninger press fitting lubricant can be used with all Conex Bänninger press fittings including >B< MaxiPro.

Conex Bänninger press fitting lubricant is non-hazardous. A safety data sheet is available at www.conexbanninger.com.



Conex | Bänninger

Conex | Bänninger
Series 3000 >B< Press Inox >B< MaxiPro >B< Flex >B< Press **Conex Compression** Conex | Bänninger
Series 4000 Triflow Solder Ring K65° >B< Press XL >B< Press Carbon Valves Conex I Bänninger

Medical Gas Delcop End Feed >B< Press Gas Series 5000 >B< ACR >B< Push >B< Press Solar Delbraze Series 8000 >B< Oyster **OEM** >B< Sonic



United Kingdom Conex Universal Limited

Spain IBP Atcosa SL Italy IBP Bänninger Italia srl USA IBP Group LLC

Germany IBP GmbH France Conex Bänninger SRL Poland Sales, Marketing and Logistics IBP Instalfittings Sp z.o.o.

China IBP China

Tel: +44 (0)121 557 2831 | Fax: +44 (0)121 557 0185 | Email: salesuk@ibpgroup.com | www.conexbanninger.com

The content of this publication is for general information only. It is the user's responsibility to determine suitability of any product for the purpose intended and reference should be made to our Technical Department if clarification is required. In the interests of technical development we reserve the right to change specification, design and materials without notice.

Conex Bänninger products are approved by numerous Standards Authorities and Certification Bodies. IBP trademarks are registered in numerous countries.

More information online at: www.conexbanninger.com